LINIAR - Modlok Bi-fold Doors

Document Q required - tick here []

ORDER FROM:	REFERENCE:		REQUIRED:		
SITE ADDRESS (IF REQD)					
Maximum sash size 1000mm x 2150mm	Clearly mark on the grid shown the configuration required. The elevation of the door is as viewed from the				
Maximum overall width 4500mm	outside. Mark along the arrows the direction that each panel has to travel.	Left Jamb	Right Jamb		
please refer to our full range of profile colours on the adjacent page	If you have 2 swing panels, indicate on this drawing which panel you would like to open first (with "FIRST")	<u>م</u>	Rigg		
Colour Outside - Smooth or Woo	odgrain	Glazed / Unglazed			
Colour Inside - Smooth or Woodgrain		Glass Type / Obscured Patten			
Bead type		Georgian, lead etc.			
Width (including extensions)		Glass spacer bar type/colour			
Height (including extensions)					
Threshold Type					
Cill size					
Drainage required					
Opens In or Out					
Internal D handle colour White	[] Gold [] Black [] Chrome]			
Main handle colour White	[] Gold [] Black [] Chrome	[] Bright Bronze []			
Cylinder type					

Liniar Bi-Fold Colour Options - Sculptured	Ovolo internal Bead	Chamfered internal Bead	
Smooth finish inside and out			
White - Solid colour	RAL: 9003	•	•
Gale Grey Smooth Foil with smooth white on inside	RAL: 7016	•	•

Woodgrain with smooth white on inside			
Rosewood	No RAL number available	•	•
Golden Oak	RAL: 8001	•	•
Black	RAL: 8022	•	•
Chartwell Green	No RAL number available	•	•
Cream	RAL: 9001	•	•
Anthracite Grey	RAL: 7016	•	•
Agate Grey (aka Painswick Green)	RAL: 7038	•	•

Woodgrain inside and out			
Cream	RAL: 9001	•	
Rosewood	No RAL number available	•	•
Golden Oak	RAL: 8001	•	•
White Ash	RAL: 9010	•	
Irish Oak	No RAL number available	•	
Anthracite Grey	RAL: 7016	•	•